



[Ceres]

100.2-167.0 watts per section

90/70/20 Δt 60°C EN442

This elegant decorative cast iron radiator, first produced in France in the 1890's, features floral scrolls flowing from top to bottom. This design is available in three heights 590mm, 780mm and 990mm.

The Ceres is one of our most popular decorative radiator designs. Although classical in style, this radiator is suited for traditional and modern properties.

Specifications

Models Available	27+
Materials	Cast Iron
Standard Finish	Black Primer
Connections	2 x 1/2" BSP connections
Pipe Centres	Width of radiator + valves
Delivery Details	Primer / colour: <15 days
Delivery Charge	£60.00 per consignment
Guarantee	10 years
Output range	300.6 – 5010 watts



[Black primer as standard]

[Any RAL colour]

[Any Farrow & Ball "Heritage" colour]

[Hand polished finish]



2 Grand Parade Polegate East Sussex BN26 5HG
 Telephone: +44 (0)1323 486848
 info@radiatorcentre.com www.radiatorcentre.com

[Ceres]

CODE	Height (mm)	Width (mm)	Depth (mm)	Projection (mm)	Sections (No)	Power (watts)	CODE	Height (mm)	Width (mm)	Depth (mm)	Projection (mm)	Sections (No)	Power (watts)	CODE	Height (mm)	Width (mm)	Depth (mm)	Projection (mm)	Sections (No)	Power (watts)
Cerus 590/3	590	216	180	212-222	3	300.6	Cerus 740/3	740	216	175	207-217	3	491.4	Cerus 990/3	990	216	180	212-222	3	501
Cerus 590/4	590	276	180	212-222	4	400.8	Cerus 740/4	740	276	175	207-217	4	655.2	Cerus 990/4	990	276	180	212-222	4	668
Cerus 590/5	590	336	180	212-222	5	501	Cerus 740/5	740	336	175	207-217	5	819	Cerus 990/5	990	336	180	212-222	5	835
Cerus 590/6	590	396	180	212-222	6	601.2	Cerus 740/6	740	396	175	207-217	6	982.8	Cerus 990/6	990	396	180	212-222	6	1002
Cerus 590/7	590	456	180	212-222	7	701.4	Cerus 740/7	740	456	175	207-217	7	1146.6	Cerus 990/7	990	456	180	212-222	7	1169
Cerus 590/8	590	516	180	212-222	8	801.6	Cerus 740/8	740	516	175	207-217	8	1310.4	Cerus 990/8	990	516	180	212-222	8	1336
Cerus 590/9	590	576	180	212-222	9	901.8	Cerus 740/9	740	576	175	207-217	9	1477.2	Cerus 990/9	990	576	180	212-222	9	1503
Cerus 590/10	590	636	180	212-222	10	1002	Cerus 740/10	740	636	175	207-217	10	1648	Cerus 990/10	990	636	180	212-222	10	1670
Cerus 590/11	590	696	180	212-222	11	1102.2	Cerus 740/11	740	696	175	207-217	11	1804.8	Cerus 990/11	990	696	180	212-222	11	1837
Cerus 590/12	590	756	180	212-222	12	1202.4	Cerus 740/12	740	756	175	207-217	12	1968.6	Cerus 990/12	990	756	180	212-222	12	2004
Cerus 590/13	590	816	180	212-222	13	1302.6	Cerus 740/13	740	816	175	207-217	13	2127.4	Cerus 990/13	990	816	180	212-222	13	2171
Cerus 590/14	590	876	180	212-222	14	1402.8	Cerus 740/14	740	876	175	207-217	14	2293.2	Cerus 990/14	990	876	180	212-222	14	2338
Cerus 590/15	590	936	180	212-222	15	1503	Cerus 740/15	740	936	175	207-217	15	2457	Cerus 990/15	990	936	180	212-222	15	2505
Cerus 590/16	590	996	180	212-222	16	1603.2	Cerus 740/16	740	996	175	207-217	16	2620.8	Cerus 990/16	990	996	180	212-222	16	2672
Cerus 590/17	590	1056	180	212-222	17	1703.4	Cerus 740/17	740	1056	175	207-217	17	2784.6	Cerus 990/17	990	1056	180	212-222	17	2839
Cerus 590/18	590	1116	180	212-222	18	1803.6	Cerus 740/18	740	1116	175	207-217	18	2948.4	Cerus 990/18	990	1116	180	212-222	18	3006
Cerus 590/19	590	1176	180	212-222	19	1903.8	Cerus 740/19	740	1176	175	207-217	19	3112.2	Cerus 990/19	990	1176	180	212-222	19	3173
Cerus 590/20	590	1236	180	212-222	20	2004	Cerus 740/20	740	1236	175	207-217	20	3276	Cerus 990/20	990	1236	180	212-222	20	3340
Cerus 590/21	590	1296	180	212-222	21	2104.2	Cerus 740/21	740	1296	175	207-217	21	3439.8	Cerus 990/21	990	1296	180	212-222	21	3507
Cerus 590/22	590	1356	180	212-222	22	2204.4	Cerus 740/22	740	1356	175	207-217	22	3603.6	Cerus 990/22	990	1356	180	212-222	22	3674
Cerus 590/23	590	1416	180	212-222	23	2304.6	Cerus 740/23	740	1416	175	207-217	23	3767.4	Cerus 990/23	990	1416	180	212-222	23	3841
Cerus 590/24	590	1476	180	212-222	24	2404.8	Cerus 740/24	740	1476	175	207-217	24	3931.2	Cerus 990/24	990	1476	180	212-222	24	4008
Cerus 590/25	590	1536	180	212-222	25	2505	Cerus 740/25	740	1536	175	207-217	25	4095	Cerus 990/25	990	1536	180	212-222	25	4175
Cerus 590/26	590	1596	180	212-222	26	2605.2	Cerus 740/26	740	1596	175	207-217	26	4258.8	Cerus 990/26	990	1596	180	212-222	26	4342
Cerus 590/27	590	1656	180	212-222	27	2705.4	Cerus 740/27	740	1656	175	207-217	27	4422.6	Cerus 990/27	990	1656	180	212-222	27	4509
Cerus 590/28	590	1716	180	212-222	28	2805.6	Cerus 740/28	740	1716	175	207-217	28	4586.4	Cerus 990/28	990	1716	180	212-222	28	4676
Cerus 590/29	590	1776	180	212-222	29	2905.8	Cerus 740/29	740	1776	175	207-217	29	4750.2	Cerus 990/29	990	1776	180	212-222	29	4843
Cerus 590/30	590	1836	180	212-222	30	3006	Cerus 740/30	740	1836	175	207-217	30	4914	Cerus 990/30	990	1836	180	212-222	30	5010



[Outputs: 90/70/20 Δt 60°C EN442]

[Dimensions in millimetres]

